




KISO 05



TECHNICAL DATA

Density:	0,10-0,15 g/cm ³
Nominal:	0,12 g/cm ³
Compressive force to reduce:	
- 25% =	2,5-3,5 N/cm ²
- 40% =	min. 7,0 N/cm ²
Hardness in shore 00:	30-40
Temp. resistance:	-50°C to +70°C
Health hazard:	None
Water absorption:	Negligible
Resistance to ozone:	Excellent

PROPERTIES

Base material:	EPDM rubber
Color:	Black and white
Adhesion:	Excellent on dry surfaces

SHELF LIFE

Up to 9 months from date of manufacture under normal storage conditions.

VARIOUS INDUSTRIES

PRODUCT

The KISO 05 Filler is a precut and self adhesive EPDM cellular rubber sealing strip.

TYPICAL APPLICATIONS

Different possible application areas within:

- > Windows and doors
- > Metal cabinets
- > Ventilation

ADVANTAGES

- > Fast, simple and clean to use
- > Very good aging properties
- > More than 40 years experience in northern climate (Scandinavia)
- > Good resistance to solvents
- > For factory as well as on site glazing
- > The product is free from harmful substances
- > Available in many dimensions

MAIN SIZES

(One pallet contains 32 cartons)

Thick-ness (mm)	Width (mm)	Meters per reel	Reels per carton	Meters per carton	Meters per pallet	Colour S=black H=white
2	8	225	6	1.350	43.200	S/H
3	8	150	6	900	28.800	S/H
4	8	125	6	750	24.000	S/H
5	8	100	6	600	19.200	S
6	8	75	6	450	14.400	S
8	10	50	6	300	9.600	S

APPLICATION

Application temperature: higher than 0°C.

Application method: by hand directly from reel.

Surface preparation: must be clean, dry, grease- and dustfree.