



BUILDING & CAMPING CAR INDUSTRIES

KISO 354



TECHNICAL DATA

Density:	1,36 g/cm ³
Needlepenetration (23°):	70 dmm
Temp. resistance:	-30°C to +80°C
Dry matter:	>99%
Health hazard:	None
Water absorption:	Negligible
Resistance to UV-light:	Excellent

PROPERTIES

Base material:	Butyl rubber
Color:	Black
Type:	Elastic-plastic
Adhesion:	Good on metal, glass, wood and concrete
Aging:	Good

SHELF LIFE

At least two years from date of manufacture under normal storage conditions.

PRODUCT

The KISO 354 Butyl is an extruded and self adhesive butyl sealing strip.

TYPICAL APPLICATIONS

Different possible application areas within:

- Roofing
- Metal constructions
- Camping cars, motorhomes and mobilehomes

ADVANTAGES

- Very good adhesion power on most materials
- No fumes, solvent free
- Non hardening, permanently elastic
- Leaves hands and application surfaces clean
- Very long durability
- Free from harmful substances
- Easy to compress

MAIN SIZES

(One pallet contains 48 cartons)

Diameter (mm)	Meter per roll	Rolls per carton	Meter per pallet	Colour
2,0	20	24	23.040	black
8,0	6	12	3.456	black

APPLICATION

Application temperature: higher than 5°C.

Application method: by hand directly from the reel; apply the KISO 354 Butyl firmly on one surface, remove the protection paper and apply the other surface firmly on the strip surface.

Surface preparation: must be clean, dry, grease- and dustfree.