



KISO 650



TECHNICAL DATA

Density:	1,3 g/cm ³
Hardness in shore °A:	either 60 or 70
Temp. resistance:	-40°C to +90°C
Health hazard:	None
Resistance to ozone:	Excellent

PROPERTIES

Base material:	EPDM rubber
Color:	Black

SHELF LIFE

Up to several years from date of manufacture under normal storage conditions.

THE WINDOW INDUSTRY

PRODUCT

The KISO 650 Profile series consists of extruded EPDM hard rubber sealing strips.

TYPICAL APPLICATIONS

Wooden windows: ensures water- and airtightness between frame and insulating glass as well as between insulating glass and beads.

Wooden conservatories: ensures water- and airtightness between fixed frames and insulating glass as well as between insulating glass and beads.

ADVANTAGES

- Enables a quick, simple and clean mounting of insulating glass
- Very good aging properties
- Good resistance to solvents
- For factory as well as on site glazing
- Comes with a cord reinforcement
- Also available with either talcum or oil on the seal surface
- The product is free from harmful substances

MAIN SIZES

(One pallet contains 20 reels)

Type	Width x height (mm)	Meters per reel	Meters per pallet
651	13,7 x 10,0	250	5.000
652	11,8 x 11,2	250	5.000

APPLICATION

Application method: by hand directly from reel.