

# KISO 358 Butyl – Double sided tape

---

## Caravans

Butyl is very widely used in connection to caravans and mobile homes. This is mainly because of the elastic abilities to absorb movements in the construction without causing leaks.

1.



2.



Sealing between the front panel and the roof panel: The sealing tape is mounted underneath the panel to ensure the sealing when water is being pushed over the window during rainfall while travelling.

3.



4.



Sealing between two overlapping side panels and / or between the panel and the decoration aluminium bar on which the windows are mounted: The sealant tape is mounted on the aluminium bar, and then over the gathering of the two panels to ensure that water cannot penetrate into the wall.

5.



6.



Sealing between the door frame and the side panel: The sealant tape is mounted onto the frame which is then applied to the wall and the sealant tape ensures that it is sealed all the way around windows and doors and the like.

## Other applications for KISO 358 Butyl

Butyl tape is used in many instances and to describe all of them is too comprehensive. Other examples are sinks, where butyl is mounted between the edges of the sink and the countertop. This ensures the sealing as well as making it possible to remove the sink relatively easy. Another example is under roofs; butyl is used to seal the roof towards to top of the wall against snow and heat loss. One more example: radon-resistant plastic sheeting; here the butyl is used to mount and seal the sheet to a concrete floor.